

Claims

We claim:

- 5 1. A container for product, comprising:
 a container body defining a space for storage of the product;
 a valve in fluid communication with the space; and
 a hollow stem in fluid communication with the valve and having an
 exterior end that has at least one side opening therethrough wherein the valve is
10 actuable to dispense product through the side opening.
2. The container of claim 1, wherein the exterior end includes a
 profiled end surface that defines the at least one side opening.
- 15 3. The container of claim 2, wherein the profiled end surface forms
 a slot.
4. The container of claim 3, wherein the slot defines first and
 second side openings.
- 20 5. The container of claim 4, wherein each of the first and second
 side openings is defined by a base surface and a pair of side surfaces
6. The container of claim 5, wherein the side surfaces are
25 substantially perpendicular to the base surface.
7. The container of claim 6, wherein the side surfaces are disposed
 at angles other than 90 degrees with respect to the base surface.
- 30 8. The container of claim 2, wherein the profiled end surface forms
 a crenellated section.

5

10

15

[illegible]

13. The container of claim 11, wherein the at least one side opening is non-circular in shape.

14. A container for use with dispensing apparatus that dispenses pressurized product stored in the container, comprising:

a container body defining a space for storage of the product;

a valve in fluid communication with the space; and

5 a hollow stem in fluid communication with the valve and having an exterior end that has at least one side opening therethrough and wherein the stem is adapted for engagement with the apparatus to permit dispensing of product through the at least one side opening into the dispensing apparatus.

10 15. The container of claim 14, wherein the exterior end includes a profiled end surface that defines the at least one side opening.

16. The container of claim 15, wherein the profiled end surface forms a slot.

15 17. The container of claim 16, wherein the slot defines first and second side openings.

20 18. The container of claim 17, wherein each of the first and second side openings is defined by a base surface and a pair of side surfaces

19. The container of claim 18, wherein the side surfaces are substantially perpendicular to the base surface.

25 20. The container of claim 19, wherein the side surfaces are disposed at angles other than 90 degrees with respect to the base surface.

30 21. The container of claim 15, wherein the profiled end surface forms a crenellated section.

22. The container of claim 15, wherein the profiled end surface forms a zig-zag section.

23. The container of claim 15, wherein the profiled end surface forms a sinusoidal section.

5 24. The container of claim 14, wherein the at least one side opening is defined by at least one wall substantially completely surrounding the opening.

25. The container of claim 24, wherein the at least one side opening is circular in shape.

10 26. The container of claim 24, wherein the at least one side opening is non-circular in shape.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

27. A combination, comprising:

a dispensing apparatus adapted to dispense product and having a coupling assembly and a dispenser inlet valve; and

5 a container of pressurized product disposed in the dispenser and engaged by the coupling assembly;

wherein the container includes a container body defining a space for storage of the product, a container valve in fluid communication with the space and a hollow stem in fluid communication with the valve wherein the hollow stem has an exterior end that has at least one side opening therethrough and wherein the hollow
10 stem is adapted for engagement with the dispenser inlet valve to permit dispensing of product through the at least one side opening into the dispensing apparatus.

28. The combination of claim 27, wherein the hollow stem includes a profiled end surface and a main body portion and wherein the coupling assembly
15 includes a first sealing element engageable with the main body portion and a second sealing element engageable with the end surface.

29. The combination of claim 28, wherein the second sealing element is spring-biased and movable from a closed position to an open position
20 when engaged by the valve.

30. The combination of claim 29, wherein the second sealing element includes a substantially spherical sealing surface.

25 31. The combination of claim 30, wherein the first sealing element forms a part of a hollow collar assembly having an interior chamber within which the second sealing element is disposed.

32. The combination of claim 31, wherein the collar assembly includes a first tapered surface and the main body portion of the valve includes a second tapered surface engageable with the first tapered surface to seal the interior chamber.

5

33. The combination of claim 32, wherein the first tapered surface and the second tapered surface are tapered at different angles.

34. The combination of claim 27, wherein the exterior end includes a slot that defines first and second side openings.

10

35. The combination of claim 34, wherein each of the first and second side openings is defined by a base surface and a pair of side surfaces substantially perpendicular to the base surface.

15

36. The combination of claim 34, wherein each of the first and second side openings is defined by a base surface and a pair of side surfaces disposed at angles other than 90 degrees with respect to the base surface.

20

37. The combination of claim 28, wherein the profiled end surface forms a crenellated section.

38. The combination of claim 28, wherein the profiled end surface forms a zig-zag section.

25

39. The combination of claim 28, wherein the profiled end surface forms a sinusoidal section.

40. The combination of claim 27, wherein the at least one side opening is defined by at least one wall substantially completely surrounding the opening.

30

41. The combination of claim 40, wherein the at least one side opening is circular in shape.

5 42. The combination of claim 40, wherein the at least one side opening is non-circular in shape.

10 43. The combination of claim 27, wherein the dispensing apparatus further includes a door movable to an open position wherein the container may be inserted into or removed from a recess of the dispenser when the door is in the open position.

15 44. The combination of claim 43, wherein the door includes walls that engage the container when the door is moved away from the open position toward a closed position as the container is being inserted into the recess.

45. The combination of claim 44, wherein the door includes a hinge.

20 46. The combination of claim 45, wherein a heater plate is disposed within the container body and wherein the plate is in contact with a heat exchanger.

47. A method of dispensing a heated gel, the method comprising the steps of:

providing a housing having a recess therein and a heater assembly disposed in the housing wherein the heater assembly includes a heater selectively operable to develop heat and a heat exchanger in heat transfer relationship with the heater and having a chamber, the heater assembly further including a first valve in fluid communication with the chamber and a second valve operable to permit fluid flow out of the chamber;

providing a container of pressurized gel, the container including a third valve and a hollow stem in fluid communication with the third valve and having at least one side opening therethrough;

placing the hollow stem in fluid communication with the first valve;
opening the first and third valves to expose the chamber to pressurized gel; and

opening the second valve to allow dispensing of gel without substantial foaming.

48. The method of claim 47, wherein the step of placing the hollow stem comprises the step of inserting the container in the recess until a coupling ring engages a coupling cap carried by the container.

49. The method of claim 48, wherein the coupling ring is urged toward a particular position by a force exerted by a spring and wherein the step of inserting includes the step of exerting pressure on the can to displace the coupling ring against the force exerted by the spring until the coupling ring travels over a flange of the coupling cap and is moved toward the particular position by the force exerted by the spring.

50. The method of claim 47, wherein the step of opening the first and third valves includes the step of maintaining the second valve in a closed condition during the opening of the first and third valves.

51. The method of claim 47, wherein the step of providing the container includes the step of forming a profiled end surface in an exterior end of the hollow stem wherein the profiled end surface defines the at least one side opening.

5 52. The method of claim 51, wherein the profiled end surface forms a slot.

53. The method of claim 52, wherein the slot defines first and second side openings.

10 54. The method of claim 53, wherein each of the first and second side openings is defined by a base surface and a pair of side surfaces

15 55. The method of claim 54, wherein the side surfaces are substantially perpendicular to the base surface.

56. The method of claim 54, wherein the side surfaces are disposed at angles other than 90 degrees with respect to the base surface.

20 57. The method of claim 51, wherein the profiled end surface forms a crenellated section.

58. The method of claim 51, wherein the profiled end surface forms a zig-zag section.

25 59. The method of claim 51, wherein the profiled end surface forms a sinusoidal section.

30 60. The method of claim 47, wherein the at least one side opening is defined by at least one wall substantially completely surrounding the opening.

61. The method of claim 60, wherein the at least one side opening is circular in shape.

62. The method of claim 60, wherein the at least one side opening is non-circular in shape.

5 63. The method of claim 47, wherein the pressurized gel includes a propellant and a soap and wherein a ratio of soap to propellant is about six or more parts of soap to one part of propellant by weight.

10 64. The method of claim 47, wherein the pressurized gel includes a propellant in a range between about 0.25 percent and about 3.50 percent by weight of a total composition of the gel.

15 65. The method of claim 64, wherein the propellant is about 2.25 percent by weight of the total composition of the gel.

66. The method of claim 47, wherein the pressurized gel includes a propellant having a vapor pressure less than or equal to about 40 psia.

20 67. The method of claim 66, wherein the propellant has a vapor pressure of about 33.7 psia.

25 68. The method of claim 47, wherein the housing further includes a door movable between an open position exposing the recess and a closed position closing off the recess wherein the door includes a wall and wherein the step of placing includes the further steps of moving the door to the open position, inserting the container into the exposed recess and closing the door when the container is partially inserted into the recess such that the wall engages the can and forces the can fully into the recess.

30 69. The method of claim 47, wherein the pressurized gel includes a single propellant.

[illegible]

71. A shave gel, comprising:

a mixture of a soap and a propellant, wherein a ratio of soap to propellant is about six or more parts of soap to one part of propellant by weight and wherein the propellant is in a range between about 0.25 percent and about 3.50 percent by weight of a total composition of the gel and the propellant has a vapor pressure less than or equal to about 40 psia.

72. The shave gel of claim 71, wherein the propellant is about 2.25 percent by weight of a total composition of the gel.

73. The shave gel of claim 72, wherein the vapor pressure of the propellant is equal to about 33.7 psia.

74. The shave gel of claim 73, in combination with a container that stores the gel under pressure.

75. The shave gel of claim 74, further in combination with a dispenser that receives the container and wherein the dispenser includes a heater assembly that heats the shave gel.

76. The shave gel of claim 75, wherein the dispenser includes a first valve in fluid communication with the container, a heat exchanger in fluid communication with the first valve and a second valve in fluid communication with the heat exchanger wherein shave gel is disposed in the heat exchanger under pressure.

77. The shave gel of claim 71, wherein the shave gel includes a single propellant.

78. The shave gel of claim 77, wherein the single propellant comprises isopentane.